

AMENDMENTS TO THE CLAIMS

1. (Currently amended) An image pick-up device comprising:

a main body including a first body having a first surface and a second body having a second surface;

a camera located on the second surface for taking a picture; and

a display device displaying a picture taken from the perspective of the camera and arranged at a the first surface of said ~~main first~~ body on the same side as said camera, wherein

said camera is fixed to said main body such that an optical axis of said camera extends in a direction different from a direction perpendicular to a display surface of said display device and the optical axis of the camera extends in a direction different from a direction perpendicular to the second surface.

2. (Original) The image pick-up device according to claim 1, wherein

said camera is arranged on one side of the vertically opposite sides of said display device, and the optical axis of said camera is inclined toward the other side.

3. (Original) The image pick-up device according to claim 1, wherein

said camera is arranged on one side of the laterally opposite sides of said display device, and the optical axis of said camera is inclined toward the other side.

4. (Original) The image pick-up device according to claim 1, wherein

said display device is a main display portion arranged on one of opposite surfaces of said main body,

said image pick-up device further comprises a sub-display portion arranged on the other surface of said main body, and

said camera and said main display portion are arranged on said one of the opposite surfaces of said main body.

5. (Original) The image pick-up device according to claim 1, further comprising:
a main display portion arranged on one of opposite surfaces of said main body; wherein
said display device is a sub-display portion arranged on the other surface of said main body, and
said camera and said sub-display portion are arranged on said other surface of said main body.

6. (Currently Amended) The image pick-up device according to claim 1, wherein
~~said main body has a structure formed of first and second bodies are foldably coupled~~
~~together, and~~
~~said camera and said display device are arranged on said first body.~~

7-8. (Cancelled)

9. (Currently Amended) The image pick-up device according to claim 1 further
comprising:
an additional camera arranged on said main body, wherein
~~said main body has a structure formed of first and second bodies foldably coupled~~
~~together, and~~
~~said camera is arranged on one of said first and second bodies, and said additional camera~~
~~is arranged on the first body, other of said first and second bodies.~~

10-11. (Cancelled)

12. (Currently Amended) The image pick-up device according to claim ~~9~~ 44, wherein
said additional camera has an optical axis perpendicular to the display surface of said
display device, and
said camera has an optical axis in a direction different from a direction perpendicular to
the display surface of the display device.

13. (Currently Amended) The image pick-up device according to claim 9, wherein said camera and said additional camera are both arranged on the same side of ~~said one of the bodies~~ the first body.

14. (Original) The image pick-up device according to claim 13, wherein one of said camera and said additional camera is arranged on one of the vertically opposite sides of said display device, and has an optical axis inclined toward the other side of said vertically opposite sides, and the other of said camera and said additional camera is arranged on one of the laterally opposite sides of said display device, and has an optical axis inclined toward the other side of said laterally opposite sides.

15. (Currently Amended) An image pick-up device comprising:
a main body having a first side and a second side including a first body having a first surface and a second body having a second surface;
a camera for taking a picture fixed to said main body first side and the second surface and having an optical axis; and
a first display device including a display surface displaying a picture taken by said camera and arranged on said first side and the first surface;
wherein said optical axis extends in a direction different from a direction perpendicular to said display surface and the optical axis of the camera extends in a direction different from a direction perpendicular to the second surface.

16. (Previously presented) The image pick-up device according to claim 15, wherein said first display device includes first and second vertically opposite sides and said camera is arranged on one of said first and second vertically opposite sides, and the optical axis of said camera is inclined toward the other of said first and second vertically opposite sides.

17. (Previously presented) The image pick-up device according to claim 15, wherein said first display device includes first and second laterally opposite sides and said camera is arranged on one of said first and second laterally opposite sides, and the optical axis of said camera is inclined toward the other of said first and second laterally opposite sides.

18. (Previously presented) The image pick-up device according to claim 15, further comprising a second display device on the second side of said main body.

19. (Previously presented) The image pick-up device according to claim 18, wherein said first display device comprises a main display portion and said second display device comprises a sub-display portion.

20. (Previously presented) The image pick-up device according to claim 18, wherein said first display device comprises a sub-display portion and said second display device comprises a main display portion.